

CIN: U33125DL1996PLC082482

MATERIAL SAFETY DATA SHEET WEMLAC PAINT STRIPPER



SECTION 1 – PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: WEMLAC PAINT STRIPPER

PRODUCT USE: Paint Stripping / Removal

MANUFACTURER: Wembley Laboratories Ltd.
Plot No. 60A, Phase-1, E.P.I.P
Jharmajri, Baddi- 173-205, HP

SECTION 2 – HAZARD IDENTIFICATION

GHS CLASSIFICATION:

	Health	Environmental	Physical
Acute Toxicity:	Category 4	Acute Toxicity: Category 3	NOT CLASSIFIED
Skin Irritation:	Category 2		
Skin Sensitization:	Category 1		
Eye:	Category 2A		
Carcinogenicity:	Category 2		

GHS LABEL:

Signal Word: Warning



WHMIS CLASSIFICATION: CLASS D, DIVISION 2A
CLASS D, DIVISION 2B

Hazard Statement

H315: Causes skin irritation
H319: Causes serious eye irritation
H332: Harmful if inhaled
H336: May cause drowsiness or dizziness
H351: Suspected of causing cancer
EUH066: Repeated exposure may cause skin dryness or cracking

Precautionary Statements

P201: Obtain special instructions before use.
P202: Do not handle until all safety precautions are understood.
P261: Avoid breathing vapours.
P271: Use only in a well-ventilated area.
P280: Wear protective gloves, clothing and eye protection.
P304+P340: IF INHALED: Move to fresh air and keep comfortable.
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes.
P501: Dispose of contents/container as per local regulations.

SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS

INGREDIENTS:	CAS#	EINECS #	CONCENTRATION
Dichloromethane	75-09-2	200-833-9	60-75 %
Formic Acid	64-18-6	200-579-1	1-5 %
Paraffin Wax	8002-74-2	232-315-6	5-15 %
Stearic Acid	57-11-4	200-313-4	1-3 %

SECTION 4 – FIRST AID MEASURES

General Advice: Remove the affected person from exposure. Keep at rest and warm. Seek medical attention if symptoms persist or in case of significant exposure.

Inhalation: Move the person to fresh air immediately. Keep comfortable for breathing. If breathing is difficult, oxygen may be given by trained personnel. If not breathing, provide artificial respiration. Seek immediate medical attention.

Skin Contact: Remove contaminated clothing and footwear. Wash skin thoroughly with soap and water. Do not use solvents or thinners. If irritation develops or persists, seek medical advice.

Eye Contact: Rinse cautiously with plenty of water for at least 15 minutes. Remove contact lenses if present and easy to do. Continue rinsing. Seek immediate medical attention.

Ingestion: Rinse mouth with water. Do NOT induce vomiting. Give water if the person is conscious. Never give anything by mouth to an unconscious person. Seek immediate medical attention.

SECTION 5 – FIREFIGHTING MEASURES

Suitable Extinguishing Media: Dry chemical powder, carbon dioxide (CO₂), foam, water fog.

Unsuitable Extinguishing Media: Do not use direct water jet.

Fire and Explosion Hazards: Product is not flammable, however on heating it may decompose and release toxic fumes such as carbon monoxide, carbon dioxide and hydrogen chloride. Vapours may accumulate in low areas.

Fire fighting Instructions: Use water spray to cool containers exposed to fire. Avoid inhalation of fumes. Prevent fire water from entering drains.

Protective Equipment for Fire fighters: Wear self-contained breathing apparatus (SCBA) and protective clothing.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Personal Precautions:

Avoid breathing vapours. Ensure adequate ventilation. Wear suitable protective equipment such as gloves and safety goggles. Avoid contact with skin and eyes.

Environmental Precautions:

Do not allow material to enter drains, surface water or soil. Inform authorities if large quantities enter the environment.

Methods for Cleaning Up: Absorb spill with inert material such as sand, earth or vermiculite. Collect in suitable containers for disposal. Clean contaminated area with water and detergent.

Additional Information: Ensure good ventilation during cleanup. Avoid ignition sources as a general precaution. Dispose of waste in accordance with local regulations.

SECTION 7 – HANDLING AND STORAGE

Handling:

Use only in well-ventilated areas. Avoid breathing vapours. Avoid contact with skin, eyes and clothing. Wear appropriate protective equipment such as gloves and safety goggles. Do not eat, drink or smoke while handling. Wash hands thoroughly after use.

Storage:

Store in a cool, dry and well-ventilated place. Keep container tightly closed when not in use. Keep away from heat and direct sunlight. Store away from incompatible materials such as strong oxidizing agents. Do not store with food or beverages.

Additional Information:

Keep containers properly labelled. Ensure good ventilation in storage areas. Use original containers or approved containers only.

SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits: Dichloromethane (DCM): TWA 50 ppm

Engineering Controls: Use in a well-ventilated area. Provide local exhaust ventilation where necessary to maintain vapour levels below exposure limits.

Personal Protective Equipment (PPE):

Eye Protection: Safety goggles or face shield

Skin Protection: Chemical-resistant gloves (e.g., nitrile, neoprene) and protective clothing

Respiratory Protection: Use suitable respirator if ventilation is inadequate

Hygiene Measures: Wash hands after handling. Do not eat, drink or smoke during use. Remove contaminated clothing and wash before reuse.

CIN: U33125DL1996PLC082482

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Viscous gel
Colour:	Clear to slightly hazy
Odour:	Characteristic solvent odour
pH:	Not applicable / Not available
Boiling Point:	Approx. 40 – 80°C
Flash Point:	Not applicable (non-flammable mixture)
Evaporation Rate:	Moderate to fast
Flammability:	Not classified as flammable
Specific Gravity:	Approx. 1.10 – 1.25
Solubility:	Partially soluble in water
Viscosity:	Gel type / high viscosity

SECTION 10 – STABILITY AND REACTIVITY

Reactivity:

No hazardous reactions expected under normal conditions of use.

Chemical Stability:

Stable under recommended storage and handling conditions.

Possibility of Hazardous Reactions:

No dangerous reactions expected under normal conditions. Avoid contact with incompatible materials.

Conditions to Avoid:

Avoid heat, open flames and direct sunlight. Avoid excessive heating and poor ventilation.

Incompatible Materials:

Strong oxidizing agents, strong bases, reactive metals such as aluminium, sodium and potassium

Hazardous Decomposition Products:

May release toxic fumes on heating or burning, including carbon monoxide, carbon dioxide, hydrogen chloride and traces of phosgene.

SECTION 11 – TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure:

Inhalation, skin contact, eye contact and ingestion.

Acute Toxicity:

Harmful if inhaled. May be harmful if swallowed or absorbed through skin.

Skin Corrosion / Irritation:

Causes skin irritation. Prolonged contact may lead to dryness or cracking.

Serious Eye Damage / Irritation:

Causes serious eye irritation.

Respiratory or Skin Sensitization:

Not expected to be a sensitizer.

Carcinogenicity:

Contains dichloromethane, which is suspected of causing cancer.

Reproductive Toxicity:

Contains formic acid. May cause adverse reproductive effects.

STOT – Single Exposure:

May cause drowsiness or dizziness.

CIN: U33125DL1996PLC082482

STOT – Repeated Exposure:

Prolonged or repeated exposure may cause damage to liver and kidneys.

Aspiration Hazard:

Not expected to present an aspiration hazard.

Symptoms Related to Exposure:

- **Inhalation:** Dizziness, headache, nausea
- **Skin Contact:** Irritation, dryness
- **Eye Contact:** Redness, watering, irritation
- **Ingestion:** Nausea, vomiting, abdominal discomfort

SECTION 12 – ECOLOGICAL INFORMATION**Ecotoxicity:**

Harmful to aquatic life. Avoid release into the environment.

Persistence and Degradability:

Product is partially biodegradable. Some components may persist in the environment.

Bioaccumulative Potential:

Low to moderate potential for bioaccumulation.

Mobility in Soil:

Product is expected to have moderate mobility in soil and may contaminate groundwater.

SECTION 13 – WASTE DISPOSAL CONSIDERATIONS

Follow local and national regulations. Consult disposal expert.

SECTION 14 – TRANSPORT INFORMATION

UN Number: UN 1593

UN Proper Shipping Name: Paint Stripper

Transport Hazard Class: 6.1 (Toxic)

Subsidiary Risk: None

Packing Group: III

Labels Required: Class 6.1 – Toxic Substance Label

Marine Pollutant: No

SECTION 15 – REGULATORY INFORMATION**Safety, Health and Environmental Regulations:**

This product is classified and labelled in accordance with the Globally Harmonized System (GHS) for classification and labelling of chemicals.

Applicable Regulations:

- Follow applicable local, national and international regulations for handling, storage and disposal
- Ensure compliance with workplace safety and environmental protection guidelines

Hazard Classification:

- Carcinogenicity – Category 2
- Acute Toxicity (Inhalation) – Category 4

CIN: U33125DL1996PLC082482

- Skin Irritation – Category 2
- Eye Irritation – Category 2A
- STOT (Single Exposure) – Category 3
- STOT (Repeated Exposure) – Category 1

Additional Information:

Users should ensure compliance with all applicable safety, health and environmental regulations relevant to the use of this product.

SECTION 16 – OTHER INFORMATION

Department Issuing Safety Data Sheet:

Wembley Laboratories Ltd – Safety & Health Department

Email Address: info@wembleysquickfix.com

Training Requirements:

Users should be trained in safe handling practices described in product literature.

Regulatory Compliance: Ingredients comply with applicable RoHS requirements.

Issue Date: January 22, 2026

Revision: 0

Intended Use: Product intended for use by trained/skilled personnel.

Disclaimer: Information is believed accurate based on current knowledge; no warranty expressed or implied. Users must determine suitability and ensure safe use.