



TECHNICAL DATA SHEET

QUICKFIX MULTIPURPOSE ADHESIVE

Wembley's QUICKFIX is India's first indigenous all-purpose adhesive. It is a quick drying, clear and transparent adhesive which exhibits excellent bonding properties. Owing to its capacity to bond most substrates, it finds applications across various industries, and well as DIY and Household use.

Area of Usage:

Joins a variety of materials such as glass, ceramic, earthenware, ivory porcelain, balsa wood, leathers, rubber, cork and most plastic like Acrylic, ABS polystyrene etc.

Used by Jewellery craftsmen for Minakari work & Fixing pearls and precious / semi-precious stones.

Widely used in industries such as speaker & remote manufacturing, electronics, electrical parts, etc.

Appearance: Colourless, Transparent to very slight yellow tinted liquid

Viscosity @ 30°C ± 2°C: 4,200 to 4,600 CPS (Tube Pack) & 5,400 to 5,800 CPS (Tin Pack)

Specific Gravity: 0.93 Approx (Tube Pack) & 0.94 Approx (Tin Pack)

Features & Benefits:

1. Clear and transparent bonding.
2. Quick Drying formula.
3. Offers excellent resistance to heat and water.
4. Bonds permanently.
5. Packed in long nozzle tubes for precise application.
6. Bonds a variety of substrates - glass, ceramic, earthenware, ivory porcelain, balsa wood, leathers, rubber, cork and most plastic like Acrylic, ABS polystyrene etc.
7. Long Shelf life - 18 months from the date of manufacturing.

DO'S & DON'TS:

Replace the cap of the container immediately after every use to avoid unnecessary evaporation of the solvent. This leads to thickening of the product. We do not recommend addition of any solvent to lower the viscosity.

The substrates to be joined together must be cleaned before applying Wembley's Quickfix. It is recommended that Quickfix must be applied to both sides.

More than 1 coat is recommended where substrates are porous in nature.

Care should be taken not to disturb or apply any force to newly assembled joints. Early handling can compromise the integrity of joints. Three hour at 30°C and 4 hours at 20°C is an indicative handling time, however this shall greatly vary depending on the substrates to be joined together.

CIN: U33125DL1996PLC082482

SHELF LIFE:

18 months from the date of manufacture in original sealed containers when stored under recommended storing conditions.

SAFETY & STORAGE:

Wembley's Quickfix should be stored in a cool & dry place. It is highly flammable hence store in a cool (<30°C) place away from open flame or electric heaters or sparks.